

IR scanner for energy meter data gateway FSDG14



AIR

Temperature at mounting location:

-20°C up to +50°C.

Storage temperature: -25°C up to +70°C.

Relative humidity:

annual average value <75%.

Magnetic infrared opto head for reading out electronic energy meters with IEC 62056-21 IR interface.

Magnetic infrared opto head for reading out electronic energy meters with IEC 62056-21 IR interface.

The AIR data interface is an infrared RS232 interface acc. to IEC 1107 or EN61107 specification with a magnetic head. The interface serves as a data-side connecting unit between the infrared port of the energy meter and the serial input of the FSDG14 data gateway.

Open, tinned cable ends for connection to the terminals of the data gateway FSDG14. Cable length 0.75 m.

Technical data

Supply voltage	+12 V DC (±10%)
----------------	-----------------

Supply by FSDG14	
------------------	--

Current consumption	10 mA
---------------------	-------

Cable colours	+12 V = yellow, GND = green, Rx = red, Tx = black
---------------	--

Rate of transmission	9600 Baud
----------------------	-----------

Wave length	940 nm
-------------	--------

Dimensions	Ø 32 mm
------------	---------

	Height 20 mm
--	--------------

	Length without cable 45 mm
--	----------------------------

protection class	IP50
------------------	------

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

☎ +49 711 94350000

www.eltako.com